

F07PVF (CHPRFS/ZHPRFS) – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

F07PVF (CHPRFS/ZHPRFS) returns error bounds for the solution of a complex Hermitian indefinite system of linear equations with multiple right-hand sides, $AX = B$, using packed storage. It improves the solution by iterative refinement, in order to reduce the backward error as much as possible.

2 Specification

```

SUBROUTINE F07PVF(UPLO, N, NRHS, AP, AFP, IPIV, B, LDB, X, LDX,
1             FERR, BERR, WORK, RWORK, INFO)
ENTRY      chprfs(UPLO, N, NRHS, AP, AFP, IPIV, B, LDB, X, LDX,
1             FERR, BERR, WORK, RWORK, INFO)
INTEGER    N, NRHS, IPIV(*), LDB, LDX, INFO
real      FERR(*), BERR(*), RWORK(*)
complex  AP(*), AFP(*), B(LDB,*), X(LDX,*), WORK(*)
CHARACTER*1 UPLO

```

The ENTRY statement enables the routine to be called by its LAPACK name.

3 Description

This routine returns the backward errors and estimated bounds on the forward errors for the solution of a complex Hermitian indefinite system of linear equations with multiple right-hand sides, $AX = B$, using packed storage. The routine handles each right-hand side vector (stored as a column of the matrix B) independently, so we describe the function of the routine in terms of a single right-hand side b and solution x .

Given a computed solution x , the routine computes the *component-wise backward error* β . This is the size of the smallest relative perturbation in each element of A and b such that x is the exact solution of a perturbed system

$$(A + \delta A)x = b + \delta b$$

$$|\delta a_{ij}| \leq \beta |a_{ij}| \quad \text{and} \quad |\delta b_i| \leq \beta |b_i|.$$

Then the routine estimates a bound for the *component-wise forward error* in the computed solution, defined by:

$$\max_i |x_i - \hat{x}_i| / \max_i |x_i|$$

where \hat{x} is the true solution.

For details of the method, see the Chapter Introduction.

4 References

- [1] Golub G H and van Loan C F (1996) *Matrix Computations* Johns Hopkins University Press (3rd Edition), Baltimore

5 Parameters

- 1: UPLO — CHARACTER*1 *Input*
On entry: indicates whether the upper or lower triangular part of A is stored and how A has been factorized, as follows:

if UPLO = 'U', then the upper triangular part of A is stored and A is factorized as $PUDU^H P^T$ where U is upper triangular;
 if UPLO = 'L', then the lower triangular part of A is stored and A is factorized as $PLDL^H P^T$ where L is lower triangular.

Constraint: UPLO = 'U' or 'L'.

- 2:** N — INTEGER *Input*
On entry: n , the order of the matrix A .
Constraint: $N \geq 0$.
- 3:** NRHS — INTEGER *Input*
On entry: r , the number of right-hand sides.
Constraint: NRHS ≥ 0 .
- 4:** AP(*) — *complex* array *Input*
Note: the dimension of the array AP must be at least $\max(1, N*(N+1)/2)$.
On entry: the n by n original Hermitian matrix A as supplied to F07PRF (CHPTRF/ZHPTRF).
- 5:** AFP(*) — *complex* array *Input*
Note: the dimension of the array AFP must be at least $\max(1, N*(N+1)/2)$.
On entry: details of the factorization of A stored in packed form, as returned by F07PRF (CHPTRF/ZHPTRF).
- 6:** IPIV(*) — INTEGER array *Input*
Note: the dimension of the array IPIV must be at least $\max(1, N)$.
On entry: details of the interchanges and the block structure of D , as returned by F07PRF (CHPTRF/ZHPTRF).
- 7:** B(LDB,*) — *complex* array *Input*
Note: the second dimension of the array B must be at least $\max(1, \text{NRHS})$.
On entry: the n by r right-hand side matrix B .
- 8:** LDB — INTEGER *Input*
On entry: the first dimension of the array B as declared in the (sub)program from which F07PVF (CHPRFS/ZHPRFS) is called.
Constraint: LDB $\geq \max(1, N)$.
- 9:** X(LDX,*) — *complex* array *Input/Output*
Note: the second dimension of the array X must be at least $\max(1, \text{NRHS})$.
On entry: the n by r solution matrix X , as returned by F07PSF (CHPTRS/ZHPTRS).
On exit: the improved solution matrix X .
- 10:** LDX — INTEGER *Input*
On entry: the first dimension of the array X as declared in the (sub)program from which F07PVF (CHPRFS/ZHPRFS) is called.
Constraint: LDX $\geq \max(1, N)$.
- 11:** FERR(*) — *real* array *Output*
Note: the dimension of the array FERR must be at least $\max(1, \text{NRHS})$.
On exit: FERR(j) contains an estimated error bound for the j th solution vector, that is, the j th column of X , for $j = 1, 2, \dots, r$.

- 12:** BERR(*) — *real* array *Output*
Note: the dimension of the array BERR must be at least $\max(1, \text{NRHS})$.
On exit: BERR(j) contains the component-wise backward error bound β for the j th solution vector, that is, the j th column of X , for $j = 1, 2, \dots, r$.
- 13:** WORK(*) — *complex* array *Workspace*
Note: the dimension of the array WORK must be at least $\max(1, 2*N)$.
- 14:** RWORK(*) — *real* array *Workspace*
Note: the dimension of the array RWORK must be at least $\max(1, N)$.
- 15:** INFO — INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

INFO < 0

If INFO = $-i$, the i th parameter had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

The bounds returned in FERR are not rigorous, because they are estimated, not computed exactly; but in practice they almost always overestimate the actual error.

8 Further Comments

For each right-hand side, computation of the backward error involves a minimum of $16n^2$ real floating-point operations. Each step of iterative refinement involves an additional $24n^2$ real operations. At most 5 steps of iterative refinement are performed, but usually only 1 or 2 steps are required.

Estimating the forward error involves solving a number of systems of linear equations of the form $Ax = b$; the number is usually 5 and never more than 11. Each solution involves approximately $8n^2$ real operations.

The real analogue of this routine is F07PHF (SSPRFS/DSPRFS).

9 Example

To solve the system of equations $AX = B$ using iterative refinement and to compute the forward and backward error bounds, where

$$A = \begin{pmatrix} -1.36 + 0.00i & 1.58 + 0.90i & 2.21 - 0.21i & 3.91 + 1.50i \\ 1.58 - 0.90i & -8.87 + 0.00i & -1.84 - 0.03i & -1.78 + 1.18i \\ 2.21 + 0.21i & -1.84 + 0.03i & -4.63 + 0.00i & 0.11 + 0.11i \\ 3.91 - 1.50i & -1.78 - 1.18i & 0.11 - 0.11i & -1.84 + 0.00i \end{pmatrix}$$

and

$$B = \begin{pmatrix} 7.79 + 5.48i & -35.39 + 18.01i \\ -0.77 - 16.05i & 4.23 - 70.02i \\ -9.58 + 3.88i & -24.79 - 8.40i \\ 2.98 - 10.18i & 28.68 - 39.89i \end{pmatrix}.$$

Here A is Hermitian indefinite, stored in packed form, and must first be factorized by F07PRF (CHPTRF/ZHPTRF).

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*   F07PVF Example Program Text
*   Mark 15 Release. NAG Copyright 1991.
*   .. Parameters ..
INTEGER          NIN, NOUT
PARAMETER       (NIN=5,NOUT=6)
INTEGER          NMAX, NRHMAX, LDB, LDX
PARAMETER       (NMAX=8,NRHMAX=NMAX,LDB=NMAX,LDX=NMAX)
*   .. Local Scalars ..
INTEGER          I, IFAIL, INFO, J, N, NRHS
CHARACTER       UPLO
*   .. Local Arrays ..
complex        AFP(NMAX*(NMAX+1)/2), AP(NMAX*(NMAX+1)/2),
+               B(LDB,NRHMAX), WORK(2*NMAX), X(LDX,NMAX)
real           BERR(NRHMAX), FERR(NRHMAX), RWORK(NMAX)
INTEGER          IPIV(NMAX)
CHARACTER       CLABS(1), RLABS(1)
*   .. External Subroutines ..
EXTERNAL        chprfs, chptrf, chptrs, F06TFF, X04DBF
*   .. Executable Statements ..
WRITE (NOUT,*) 'F07PVF Example Program Results'
*   Skip heading in data file
READ (NIN,*)
READ (NIN,*) N, NRHS
IF (N.LE.NMAX .AND. NRHS.LE.NRHMAX) THEN
*
*       Read A and B from data file, and copy A to AFP and B to X
*
      READ (NIN,*) UPLO
      IF (UPLO.EQ.'U') THEN
          READ (NIN,*) ((AP(I+J*(J-1)/2),J=I,N),I=1,N)
      ELSE IF (UPLO.EQ.'L') THEN
          READ (NIN,*) ((AP(I+(2*N-J)*(J-1)/2),J=1,I),I=1,N)
      END IF
      READ (NIN,*) ((B(I,J),J=1,NRHS),I=1,N)
      DO 20 I = 1, N*(N+1)/2
          AFP(I) = AP(I)
20  CONTINUE
      CALL F06TFF('General',N,NRHS,B,LDB,X,LDX)
*
*       Factorize A in the array AFP
*
      CALL chptrf(UPLO,N,AFP,IPIV,INFO)
*
      WRITE (NOUT,*)
      IF (INFO.EQ.0) THEN
*
*           Compute solution in the array X
*
          CALL chptrs(UPLO,N,NRHS,AFP,IPIV,X,LDX,INFO)
*
*           Improve solution, and compute backward errors and
*           estimated bounds on the forward errors
*
          CALL chprfs(UPLO,N,NRHS,AP,AFP,IPIV,B,LDB,X,LDX,FERR,BERR,

```

```

+           WORK,RWORK,INFO)
*
*           Print solution
*
          IFAIL = 0
          CALL X04DBF('General',' ',N,NRHS,X,LDX,'Bracketed','F7.4',
+                   'Solution(s)','Integer',RLABS,'Integer',CLABS,
+                   80,0,IFAIL)
          WRITE (NOUT,*)
          WRITE (NOUT,*) 'Backward errors (machine-dependent)'
          WRITE (NOUT,99999) (BERR(J),J=1,NRHS)
          WRITE (NOUT,*)
+         'Estimated forward error bounds (machine-dependent)'
          WRITE (NOUT,99999) (FERR(J),J=1,NRHS)
        ELSE
          WRITE (NOUT,*) 'The factor D is singular'
        END IF
      END IF
    STOP
  *
99999 FORMAT ((5X,1P,4(e11.1,7X)))
      END

```

9.2 Program Data

F07PVF Example Program Data

```

  4  2                                     :Values of N and NRHS
  'L'                                     :Value of UPLO
(-1.36, 0.00)
( 1.58,-0.90) (-8.87, 0.00)
( 2.21, 0.21) (-1.84, 0.03) (-4.63, 0.00)
( 3.91,-1.50) (-1.78,-1.18) ( 0.11,-0.11) (-1.84, 0.00) :End of matrix A
( 7.79,  5.48) (-35.39, 18.01)
(-0.77,-16.05) (  4.23,-70.02)
(-9.58,  3.88) (-24.79, -8.40)
( 2.98,-10.18) ( 28.68,-39.89)                                     :End of matrix B

```

9.3 Program Results

F07PVF Example Program Results

Solution(s)

```

           1           2
1 ( 1.0000,-1.0000) ( 3.0000,-4.0000)
2 (-1.0000, 2.0000) (-1.0000, 5.0000)
3 ( 3.0000,-2.0000) ( 7.0000,-2.0000)
4 ( 2.0000, 1.0000) (-8.0000, 6.0000)

```

Backward errors (machine-dependent)

```

      8.5E-17      8.3E-17

```

Estimated forward error bounds (machine-dependent)

```

      2.4E-15      3.2E-15

```