G01EFF - NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

G01EFF returns the lower or upper tail probability of the gamma distribution, with parameters α and β , via the routine name.

2 Specification

real FUNCTION GO1EFF(TAIL, G, A, B, IFAIL)

3 Description

The lower tail probabilty for the gamma distribution with parameters α and β , $P(G \leq g)$, is defined by:

$$P(G \le g; \alpha, \beta) = \frac{1}{\beta^{\alpha} \Gamma(\alpha)} \int_0^g G^{\alpha - 1} e^{-G/\beta} dG , \quad \alpha > 0.0 , \beta > 0.0$$

The mean of the distribution is $\alpha\beta$ and its variance is $\alpha\beta^2$. The transformation $Z = \frac{G}{\beta}$ is applied to yield the following incomplete gamma function in normalised form,

$$P(G \le g; \alpha, \beta) = P(Z \le g/\beta : \alpha, 1.0) = \frac{1}{\Gamma(\alpha)} \int_0^{g/\beta} Z^{\alpha - 1} e^{-Z} dZ.$$

This is then evaluated using S14BAF.

4 References

[1] Hastings N A J and Peacock J B (1975) Statistical Distributions Butterworths

5 Parameters

1: TAIL — CHARACTER*1

Input

On entry: indicates whether an upper or lower tail probability is required.

If TAIL = 'L', then the lower tail probability is returned, that is $P(G \leq g : \alpha, \beta)$.

If TAIL = 'U', then the upper tail probability is returned, that is $P(G \ge g : \alpha, \beta)$.

Constraint: TAIL = 'L' or 'U'.

2: G-real

Input

On entry: the value of the gamma variate, g.

Constraint: $G \ge 0.0$.

3: A-real

Input

On entry: the parameter α of the gamma distribution.

Constraint: A > 0.0.

[NP3390/19/pdf] G01EFF.1

4: B-real

On entry: the parameter β of the gamma distribution.

Constraint: B > 0.0.

5: IFAIL — INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. For users not familiar with this parameter (described in Chapter P01) the recommended value is 0.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors detected by the routine:

If IFAIL = 1, 2, 3 or 4 on exit, then G01EFF returns 0.0.

IFAIL = 1

On entry, $TAIL \neq L'$ or U'.

IFAIL = 2

On entry, G < 0.0.

IFAIL = 3

On entry, $A \le 0.0$, or $B \le 0.0$.

IFAIL = 4

The solution did not converge in 600 iterations. See S14BAF. The probability returned should be a reasonable approximation to the solution.

7 Accuracy

The result should have a relative accuracy of *machine precision*. There are rare occasions when the relative accuracy attained is somewhat less than *machine precision* but the error should not exceed more than 1 or 2 decimal places. Note also that there is a limit of 18 decimal places on the achievable accuracy, because constants in S14BAF are given to this precision.

8 Further Comments

The time taken by the routine varies slightly with the input parameters g, α and β .

9 Example

The example program reads in values for several gamma distributions, computes and prints the lower probabilities for each case, until the end of data is reached.

G01EFF.2 [NP3390/19/pdf]

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
G01EFF Example Program Text
     Mark 14 Release. NAG Copyright 1989.
      .. Parameters ..
     INTEGER
                      NIN, NOUT
     PARAMETER
                      (NIN=5, NOUT=6)
      .. Local Scalars ..
     real
                      A, B, G, P
     INTEGER
                       IFAIL
      .. External Functions ..
     real
                      G01EFF
     EXTERNAL
                       G01EFF
      .. Executable Statements ..
     WRITE (NOUT,*) 'G01EFF Example Program Results'
     Skip heading in data file
     READ (NIN,*)
     WRITE (NOUT,*)
     WRITE (NOUT,*)
     + 'Gamma deviate
                         Alpha
                                    Beta Lower tail prob.'
     WRITE (NOUT,*)
  20 READ (NIN,*,END=40) G, A, B
     IFAIL = 0
     P = G01EFF('Lower',G,A,B,IFAIL)
     WRITE (NOUT, 99999) G, A, B, P
     GO TO 20
  40 STOP
99999 FORMAT (1X,F9.2,F13.2,F9.2,F14.4)
```

9.2 Program Data

Examp	le Prog	gram Data			
4.0	2.0		: G	Α	В
4.0	1.0		: G	Α	В
1.0	2.0		: G	Α	В
2.0	2.0		: G	Α	В
	4.0 4.0 1.0	Example Prog 4.0 2.0 4.0 1.0 1.0 2.0 2.0 2.0	4.0 1.0 1.0 2.0	4.0 2.0 :G 4.0 1.0 :G 1.0 2.0 :G	4.0 2.0 :G A 4.0 1.0 :G A 1.0 2.0 :G A

9.3 Program Results

GO1EFF Example Program Results

Gamma deviate	Alpha	Beta	Lower tail prob.
15.50	4.00	2.00	0.9499
0.50	4.00	1.00	0.0018
10.00	1.00	2.00	0.9933
5.00	2.00	2.00	0.7127

[NP3390/19/pdf] G01EFF.3 (last)